













Price Lists 03/04/2026






| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|--|---------------------|---|----------------------|
|  | 2111221LD100 | <p>VENTS AXIAL FAN 100 LD (WITH FLAT PANEL)</p> <p>Voltage: 220-240 V Power consumption: 14 W Air capacity: 88 m³/h RPM: 2300 min-1</p> | 28,35 |
|  | 2111221LD125Q | VENTS AXIAL WALL FAN 125 LD Q (WITH FLAT FACE PANEL) | 34,02 |
|  | 2111221LDAT100 | VENTS AXIAL WALL FAN 100 LDAT (WITH FLAT FACE PANEL) | 28,35 |
|  | 2111221LDT100 | VENTS AXIAL WALL FAN 100 LDT (WITH FLAT FACE PANEL) | 36,00 |
|  | 2111221LDT100FRTIME | AXIAL WALL FAN 100 LDT (W QUARTZ CLOCK) fresh time **OFFER-NET** | 19,55 |
|  | 2111221LDT150 | VENTS AXIAL WALL FAN 150 LDT (WITH FLAT FACE PANEL) | 49,00 |









Price Lists 03/04/2026

| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|--|-------------------|---|----------------------|
|  | 2111221LDTHQ100AM | VENTS AXIAL FAN 100 LDTH Q ALUM.MAT. | 58,97 |
|  | 2111221M100 | VENTS AXIAL WALL FAN 100 M Voltage: 220-240 V Power consumption: 14 W Air capacity: 98 m ³ /h RPM: 2300 min-1 | 23,81 |
|  | 2111221MA100 | VENTS AXIAL WALL FAN 100 MA (WITH AUTOMATIC SHUTTERS) Voltage: 220-240 V Power consumption: 18 W Air capacity: 98 m ³ /h RPM: 2300 min-1 | 25,00 |
|  | 2111221MA125Q | VENTS AXIAL WALL FAN 125 MA Q (WITH AUTOMATIC SHUTTERS) | 31,00 |
|  | 2111221MAT125 | VENTS AXIAL WALL FAN 125 MAT (WITH AUTOMATIC SHUTTERS) | 31,00 |
|  | 2111221MAT150 | VENTS AXIAL WALL FAN 150 MA T (WITH AUTOMATIC SHUTTERS) | 42,00 |

Price Lists 03/04/2026

| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|--|------------------|--|----------------------|
|  | 2111221MT100 | VENTS AXIAL WALL FAN 100 MT | 32,89 |
|  | 2111221MT150 | VENTS AXIAL WALL FAN 150 MT | 52,16 |
|  | 2111221S100 | VENTS AXIAL WALL FAN 100 S Axial fans for exhaust ventilation Maximum airflow: 95 m ³ /h Sound pressure level LpA at 3 m: 34 dB(A) Motor type: AC Casing material: Plastic | 16,28 |
|  | 2111221S100TURBO | VENTS AXIAL WALL FAN 100 S TURBO | 26,99 |
|  | 2111221S125Q | VENTS AXIAL WALL FAN 125 SQ | 21,00 |
|  | 2111221SMT100 | VENTS AXIAL WALL FAN 100 SILENTA-MT Voltage: 220-240 V Power consumption: 7 W Air capacity: 78 m ³ /h | 36,29 |

Price Lists 03/04/2026


| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|--|-------------------|---|----------------------|
|  <p>VENTS 150 MT Silenta</p> | 2111221SMT150 | <p>VENTS AXIAL WALL FAN 150 SILENTA-MT</p> <p>Voltage: 220-240V Power consumption: 20W Air capacity: 242m3/hr Power consumption 20W</p> | 62,37 |
|  <p>AXIAL WALL FAN 125 SOLID AND SILENT</p> | 2111221SOLID125 | <p>VENTS AXIAL WALL FAN 125 SOLID AND SILENT</p> <p>Residential fan solid and silent</p> | 25,00 |
|  <p>AXIAL WALL FAN 125T SOLID AND SILENT WITH TIMER</p> | 2111221SOLID125T | <p>VENTS AXIAL WALL FAN 125T SOLID AND SILENT WITH TIMER</p> <p>Residential fan solid and silent</p> | 28,50 |
|  <p>AXIAL WALL FAN 125T SOLID AND SILENT +TIMER +HUMIDITY SENSOR</p> | 2111221SOLID125TH | <p>VENTS AXIAL WALL FAN 125T SOLID AND SILENT +TIMER +HUMIDITY SENSOR</p> <p>Residential fan solid and silent</p> | 32,00 |
|  <p>S SERIES</p> | 2111221ST100 | <p>VENTS AXIAL WALL FAN 100 ST</p> | 23,25 |
|  <p>S SERIES</p> | 2111221STH100 | <p>VENTS AXIAL WALL FAN 100 STH</p> | 26,00 |

Price Lists 03/04/2026






| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|--|------------------|--|----------------------|
|  | 2111221STH125 | VENTS AXIAL WALL FAN 125 STH | 29,00 |
| | 2111221STH150 | VENTS AXIAL WALL FAN 150 STH | 35,00 |
|  | 2111221X100Q | VENTS AXIAL WALL FAN 100 X Q | 28,35 |
|  | 2111221X125Q | VENTS AXIAL WALL FAN 125 X Q **OFFER-NET** | 9,96 |
|  | 2111221X150Q | VENTS AXIAL WALL FAN 150 X Q | 45,36 |
|  | 2111221XSTAR100Q | VENTS AXIAL WALL FAN 100 X-STAR Q | 37,42 |
|  | 2111523ES100PIR | SLIM WALL AXIAL FAN E-STYLE 100PIR **OFFER-NET** | 29,00 |







Price Lists 03/04/2026

| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|---|-----------------|---|----------------------|
|  <p>E STYLE 2111</p> | 2111523ES150PRO | SLIM WALL AXIAL FAN E-STYLE 150 PRO **OFFER-NET** | 71,44 |
|  <p>E SMILE 2111</p> | 2111523SM100 | E-SMILE CM 100 **OFFER-NET** | 23,00 |
|  <p>IN LINE FAN QUIETLINE 100 T 2112</p> | 2112221QU100T | VENTS IN LINE FAN QUIETLINE 100 T Sound pressure level LpA at 3 m: 25 dB(A) Motor type: AC Casing material: Plastic Backdraft protection: Backdraft damper Timer: Turn off timer | 37,00 |
|  <p>TT 2112</p> | 2112221TT100 | VENTS MIXED FLOW FAN TT100 Inline mixed flow fan Sound pressure level at 3 m distance: 27 - 36 dBA Power consumption: 21- 33 W Maximum air capacity: 145 - 187 m³/h RPM: 2180 - 2385 min-1 | 53,30 |
|  <p>TT 2112</p> | 2112221TT100T | VENTS MIXED FLOW FAN TT100 TIMER Inline mixed flow fan with time delay Sound pressure level at 3 m distance: 27 - 36 dBA Power consumption: 21- 33 W Maximum air capacity: 145 - 187 m³/h RPM: 2180 - 2385 min-1 | 72,58 |

Price Lists 03/04/2026

| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|--|----------------|--|----------------------|
|  | 2112221TT125 | <p>VENTS MIXED FLOW FAN TT125</p> <p>Inline mixed flow fan</p> <p>Voltage: 1~230 V Maximum air capacity: 220 - 280 m³/h Power consumption:23 - 37 W RPM: 1950 - 2455 min-1</p> | 57,83 |
|  | 2112221TT125S | <p>VENTS MIXED FLOW FAN TT125 S</p> <p>Inline mixed flow fan</p> <p>Voltage: 1~230 V Maximum air capacity: 295 - 440 m³/h Power consumption: 32 - 60 W RPM: 1850 - 2510 min-1</p> | 79,38 |
|  | 2112221TT125ST | <p>VENTS MIXED FLOW FAN TT125 ST</p> | 107,00 |
|  | 2112221TT125T | <p>VENTS MIXED FLOW FAN TT125 TIMER</p> <p>Inline mixed flow fan with time delay</p> <p>Voltage: 1~230 V Maximum air capacity: 220 - 280 m³/h Power consumption:23 - 37 W RPM: 1950 - 2455 min-1</p> | 75,98 |
|  | 2112221TT125U | <p>VENTS MIXED FLOW FAN TT125 U with temp sensor</p> | 96,39 |

Price Lists 03/04/2026

| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|--|------------------|---|----------------------|
|  <p>TT</p> | 2112221TT150 | <p>VENTS MIXED FLOW FAN TT150</p> <p>Inline mixed flow fan</p> <p>Voltage: 1~230 V Maximum air capacity: 405 - 520 m³/h Power consumption:29 - 60 W RPM: 1680 - 2460 min-1</p> | 102,06 |
|  <p>TT</p> | 2112221TT200U | <p>VENTS MIXED FLOW FAN TT200 U **OFFER **OFFER-NET**</p> | 70,55 |
|  <p>TT PRO</p> | 2112221TTPRO100 | <p>VENTS INLINE MIXED-FLOW FAN TT100 PRO</p> <p>Inline mixed flow fan</p> <p>Voltage: 1~230 V Sound pressure level at 3 m distance: 27 - 32 dBA Power consumption: 23 - 25 W Maximum air capacity: 180 - 245 m³/h RPM: 2050 -2620 min-1</p> | 86,10 |
|  <p>TT PRO</p> | 2112221TTPRO200T | <p>VENTS INLINE MIXED-FLOW FAN TT200 PRO TIMER</p> <p>Voltage: 230V Power: 76-108W Current: 0.34-0.48A Max, Air Flow: 830-1040 m³/h RPM: 1915-2380 mn-1 Noise Level at 3m: 39-45dBA Transported Air Temp.: 60o SEC Class: B Protection Rating: IPX4 T: Adjustable timer from 2 to 30 minutes</p> | 187,11 |



Price Lists 03/04/2026




| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|---|------------------|---|----------------------|
|  <p>TT PRO</p> | 2112221TTPRO250T | <p>VENTS INLINE MIXED-FLOW FAN TT250 PRO TIMER</p> <p>Voltage: 230V Power: 125-177W Current: 0.54-0.79A Max, Air Flow: 1110-1400 m3/h RPM: 1955-2440 mn-1 Noise Level at 3m: 44-51dBA Transported Air Temp.: 60o Protection Rating: IPX4 T: Adjustable timer from 2 to 30 minutes</p> | 255,15 |
|  <p>TT PRO</p> | 2112221TTPRO315 | <p>VENTS INLINE MIXED-FLOW FAN TT315 PRO</p> <p>Voltage: 230V Power: 230-320W Current: 1.0-1.42A Max, Air Flow: 1570-2050 m3/h RPM: 1890-2430 mn-1 Noise Level at 3m: 41-52dBA Transported Air Temp.: 60o Protection Rating: IPX4</p> | 312,98 |
|  <p>TT Silent-M</p> | 2112221TTSM100 | <p>VENTS INLINE MIXED-FLOW FAN TT SILENT-M 100</p> <p>Inline mixed-flow fans in sound- and heat-insulated casing</p> <p>Voltage: 230V Power consumption: 24-26W Air capacity: 170 (exhaust)-240 (supply) m3/hr RPM: 2030-2630 min-1</p> | 167,00 |
|  <p>TT Silent-M</p> | 2112221TTSM100T | <p>VENTS INLINE MIXED-FLOW FAN TT SILENT-M 100 T</p> <p>Inline mixed-flow fans in sound- and heat-insulated casing with time delay</p> <p>Voltage: 230V Power consumption: 24-26W Air capacity: 170 (exhaust)-240 (supply) m3/hr RPM: 2030-2630 min-1</p> | 185,00 |

Price Lists 03/04/2026

| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|--|-----------------|--|----------------------|
|  <p>TT Silent-M</p>  | 2112221TTSM125 | <p>VENTS INLINE MIXED-FLOW FAN TT SILENT-M 125</p> <p>Inline mixed-flow fans in sound- and heat-insulated casing.</p> <p>Voltage: 230V Power consumption: 25-29W Air capacity: 230 (exhaust)-340 (supply) m3/hr RPM: 2650-2310 min-1</p> | 170,00 |
|  <p>TT Silent-M</p>  | 2112221TTSM125T | <p>VENTS INLINE MIXED-FLOW FAN TT SILENT-M 125 T</p> <p>Inline mixed-flow fans in sound- and heat-insulated casing with time delay</p> <p>Voltage: 230V Power consumption: 25-29W Air capacity: 230 (exhaust)-340 (supply) m3/hr RPM: 2650-2310 min-1</p> | 187,00 |
|  <p>TT Silent-M</p>  | 2112221TTSM150 | <p>VENTS INLINE MIXED-FLOW FAN TT SILENT-M 150</p> <p>Inline mixed-flow fans in sound- and heat-insulated casing.</p> <p>Voltage: 230V Power consumption: 45-52W Air capacity: 405 (exhaust)-555 (supply) m3/hr RPM: 1970-2645 min-1</p> | 213,00 |
|  <p>TT Silent-M</p>  | 2112221TTSM150T | <p>VENTS INLINE MIXED-FLOW FAN TT SILENT-M 150 T</p> <p>Inline mixed-flow fans in sound- and heat-insulated casing with time delay.</p> <p>Voltage: 230V Power consumption: 45-52W Air capacity: 405 (exhaust)-555 (supply) m3/hr RPM: 1970-2645 min-1</p> | 230,00 |





Price Lists 03/04/2026

| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|---|-----------------|---|----------------------|
|  <p>TT Silent-M</p> <p><small>BLAUBERG VENTS 2112</small></p> | 2112221TTSM200 | <p>VENTS INLINE MIXED-FLOW FAN TT SILENT-M 200</p> <p>Inline mixed-flow fans in sound- and heat-insulated casing.</p> <p>Voltage: 230V Power consumption: 78-110W Air capacity: 810 (exhaust)-1020 (supply) m3/hr RPM: 2015-2445 min-1</p> | 258,00 |
|  <p>TT Silent-M</p> <p><small>BLAUBERG VENTS 2112</small></p> | 2112221TTSM200T | <p>VENTS INLINE MIXED-FLOW FAN TT SILENT-M 200 T</p> <p>Inline mixed-flow fans in sound- and heat-insulated casing with time delay</p> <p>Voltage: 230V Power consumption: 78-110W Air capacity: 810 (exhaust)-1020 (supply) m3/hr RPM: 2015-2445 min-1</p> | 277,00 |
|  <p>VKM</p> <p><small>BLAUBERG VENTS 2112</small></p> | 2112221VKM100 | <p>VENTS CENTRIFUGAL IN-LINE VKM 100</p> | 142,88 |
|  <p>VKM</p> <p><small>BLAUBERG VENTS 2112</small></p> | 2112221VKM150 | <p>VENTS CENTRIFUGAL IN-LINE VKM 150</p> | 165,56 |
|  <p>VENTS CENTRIFUGAL IN-LINE VKM 160 GREY</p> <p><small>BLAUBERG VENTS</small></p> | 2112221VKM160 | <p>VENTS CENTRIFUGAL IN-LINE VKM 160 GREY</p> | 55,00 |



Price Lists 03/04/2026

| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|---|------------------|---|----------------------|
|  <p>VKM</p> | 2112221VKM200 | VENTS CENTRIFUGAL IN-LINE VKM 200 | 216,59 |
|  | 2112221VKO1K100T | VENTS VENTILATION 100 VKO1k TURBO Axial inline fan Voltage: 220-240 V Sound pressure level at 3 m distance: 37 dBA Power consumption: 16 W Maximum air capacity: 137 m³/h RPM: 2300 min-1 | 26,08 |
|  | 2112221VKO1K125 | VENTS AXIAL IN-LINE FAN 125 VKO1K | 24,95 |
|  | 2112221VKO1T125T | VENTS VENTILATION 125 VKO1T TURBO Axial inline fan Voltage: 220-240 V Sound pressure level at 3 m distance: 39 dBA Power consumption: 24 W Maximum air capacity: 245 m³/h RPM: 2400 min-1 | 35,15 |
|  | 2112221VKO1TK125 | VENTS AXIAL IN-LINE FAN 125 VKO1TK | 31,75 |



Price Lists 03/04/2026

| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|--|--------------------|---|----------------------|
|  | 2112222ISOPRIMO200 | BLAUBERG SOUND INSULATED MIXED-FLOW FAN ISO PRIMO 200 | 238,00 |
|  | 2112222TU100 | BLAUBERG TURBO 100 | 74,00 |
|  | 2112222TU100T | BLAUBERG TURBO 100 T | 89,00 |
|  | 2112222TU125T | BLAUBERG TURBO 125 T | 92,00 |
|  | 2112222TU150 | BLAUBERG TURBO 150 | 101,45 |
|  | 2112222TU150T | BLAUBERG TURBO 150 T | 122,00 |
| | | | |

Price Lists 03/04/2026





| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|--|-------------------|--|----------------------|
|  <p>TURBO 200</p> | 2112222TU200 | <p>BLAUBERG TURBO 200</p> <p>Inline mixed-flow fan</p> <p>Voltage: 230V Power consumption: 76-108W Air capacity: 805 (exhaust)-1080 (supply) m3/hr RPM: 1915-2380 min-1</p> | 125,00 |
|  <p>TURBO 250</p> | 2112222TU250 | <p>BLAUBERG TURBO 250</p> <p>Inline mixed-flow fan</p> <p>Voltage: 220-2400V Power consumption: 125-177W Air capacity: 1070 min - 1360 max m3/hr RPM: 1955-2440 min-1</p> | 235,00 |
|  <p>WAVE</p> | 2112222WAVE100125 | <p>BLAUBERG SOUND INSULATED MIXED-FLOW FAN IN WAVE 100/125</p> | 155,00 |
|  <p>WAVE</p> | 2112222WAVE150160 | <p>BLAUBERG SOUND INSULATED MIXED-FLOW FAN IN WAVE 150/160</p> | 179,00 |
|  | 2112428SEGS100S | <p>IN LINE FAN SEG SILENT - 100S</p> <p>Air flow: Min 133 - Max 180 m3/hr Noise (dB 3m): Min 26 - Max 31 Power: Min 20 - Max 40 Watt Dimensions: L = 246, W = 188, H = 160 mm Weight: 1.3 kg</p> | 52,92 |



Price Lists 03/04/2026





| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|--|-----------------|--|----------------------|
|  <p>LINE-METAL 2112</p> | 2112522LM100A | DYNAIR LINE-METAL 100A FAN V230 | 104,33 |
|  <p>LINE-METAL 2112</p> | 2112523AXC100A | ELICENT FAN AXC 100A | 85,05 |
|  <p>LINE-METAL 2112</p> | 2112523AXC125B | ELICENT FAN AXC 125 B | 96,39 |
|  | 2112583LINQ125 | VORTICE SOUND-PROOF MIXED FLOW FAN LINEO 125 QUIET | 141,00 |
|  | 2112583LINQ125T | VORTICE SOUND-PROOF MIXED FLOW FAN LINEO 125 T QUIET With time delay | 160,00 |
|  <p>KSB 2121</p> | 2121221KSB100 | VENTS SOUND INSULATED BOX FAN KSB100 Compact inline sound- and heat-insulated centrifugal fan with back-curved impeller blades Voltage: 230 V Sound pressure level at 3 m distance: 33 - 34 dBA Power consumption: 73 - 77 W Maximum air capacity: 240 - 255 m³/h RPM: 2560 - 2690 min-1 | 203,72 |

Price Lists 03/04/2026







| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|---|------------------|--|----------------------|
| <p>SOUND INSULATED BOX FAN KSB100 K2</p>  <p>VENTS</p> | 2121221KSB100K2 | <p>VENTS SOUND INSULATED BOX FAN KSB100 K2</p> <p>Compact inline sound- and heat-insulated centrifugal fan with back-curved impeller blades</p> <p>Voltage: 230 V Sound pressure level at 3 m distance: 33 - 34 dBA Power consumption: 73 - 77 W Maximum air capacity: 240 - 255 m³/h RPM: 2560 - 2690 min⁻¹</p> | 125,00 |
| <p>SOUND INSULATED BOX FAN KSB125 K2</p>  <p>VENTS</p> | 2121221KSB125K2 | <p>VENTS SOUND INSULATED BOX FAN KSB125 K2</p> <p>Inline centrifugal fans in heat- and sound-insulated casing Maximum airflow: 330 m³/h</p> | 140,00 |
| | 2121221KSB125K2S | <p>VENTS SOUND INSULATED BOX FAN KSB125 K2 S - HIGH POWERED MOTOR</p> <p>Inline centrifugal fans in heat- and sound-insulated casing Maximum airflow: 484 m³/h Sound pressure level LpA at 3 m: 40 dB(A)</p> | 160,00 |
| <p>KSB</p>  <p>BLAUBERG VENTS 2121</p> | 2121221KSB150 | <p>VENTS SOUND INSULATED BOX FAN KSB150</p> <p>Compact inline sound- and heat-insulated centrifugal fan with back-curved impeller blades</p> <p>Voltage: 230V Power consumption: 72-76W Air capacity: 420 (exhaust)-435 (supply) m³/hr RPM: 2600-2720 min⁻¹</p> | 221,13 |
| <p>SOUND INSULATED BOX FAN KSB150 K2</p>  <p>VENTS</p> | 2121221KSB150K2 | <p>VENTS SOUND INSULATED BOX FAN KSB150 K2</p> <p>Inline centrifugal fans in heat- and sound-insulated casing Maximum airflow: 485 m³/h Sound pressure level LpA at 3 m: 38 dB(A)</p> | 170,00 |



Price Lists 03/04/2026

| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|---|-----------------|---|----------------------|
| <p>SOUND INSULATED BOX FAN KSB160 K2</p>  <p>VENTS</p> | 2121221KSB160K2 | <p>VENTS SOUND INSULATED BOX FAN KSB160 K2</p> <p>Inline centrifugal fans in heat- and sound-insulated casing Maximum airflow: 500 m3/h Sound pressure level LpA at 3 m: 38 dB(A)</p> | 180,00 |
| | 2121221KSB200K2 | <p>VENTS SOUND INSULATED BOX FAN KSB200 K2</p> <p>Inline centrifugal fans in heat- and sound-insulated casing Maximum airflow: 770 m3/h Sound pressure level LpA at 3 m: 42 dB(A)</p> | 250,00 |
| <p>KSB</p>  <p>ErP 2019 ErP 2019</p> <p>BLAUBERG VENTS 2121</p> | 2121221KSB200S | <p>VENTS SOUND INSULATED BOX FAN KSB200S</p> <p>Compact inline sound- and heat-insulated centrifugal fan with back-curved impeller blades</p> <p>Voltage: 230 V Power consumption: 195 - 1232 W Air capacity: 950 (exhaust) - 960 (supply) m3/hr RPM: 2570 - 2690 min-1</p> | 280,10 |
| <p>KSB</p>  <p>ErP 2019 ErP 2019</p> <p>BLAUBERG VENTS 2121</p> | 2121221KSB250 | <p>VENTS SOUND INSULATED BOX FAN KSB250</p> <p>Compact inline sound- and heat-insulated centrifugal fan with back-curved impeller blades</p> <p>Voltage: 230 V Power consumption: 198 - 238 W Air capacity: 1300 (exhaust) - 1315 (supply) m3/hr RPM: 2420 - 2730 min-1</p> | 300,86 |
| <p>SOUND INSULATED BOX FAN KSB250 K2</p>  <p>VENTS</p> | 2121221KSB250K2 | <p>VENTS SOUND INSULATED BOX FAN KSB250 K2</p> <p>Inline centrifugal fans in heat- and sound-insulated casing Maximum airflow: 1515 m3/h Sound pressure level LpA at 3 m: 45 dB(A) Sound insulation</p> | 300,00 |

Price Lists 03/04/2026

| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|--|---------------------|---|----------------------|
|  | 2121221KSB315K2S | <p>VENTS SOUND INSULATED BOX FAN KSB315 K2 S - HIGH POWERED MOTOR</p> <p>Inline centrifugal fans in heat- and sound-insulated casing Maximum airflow: 2710 m3/h Sound pressure level LpA at 3 m: 48 dB(A)</p> | 434,00 |
|  | 2121221KSB355K2 | <p>VENTS SOUND INSULATED BOX FAN KSB355 K2</p> <p>Inline centrifugal fans in heat- and sound-insulated casing Maximum airflow: 2235 m3/h Sound pressure level LpA at 3 m: 48 dB(A)</p> | 350,00 |
|  | 2121221KSB400K2 | <p>VENTS INLINE CENTRIFUGAL FAN IN INSULATED CASING KSB 400 K2</p> | 691,20 |
|  | 2121221KSB450K2Q | <p>VENTS SOUND INSULATED BOX FAN KSB450 K2 Q - LOW NOISE</p> <p>Inline centrifugal fan in heat- and sound-insulated casing with air flow up to 2760 m³/h. Q: low noise and low-powered motor</p> | 615,00 |
|  | 2121221KSB500K2230V | <p>VENTS INLINE CENTRIFUGAL FAN IN INSULATED CASING KSB 500 K2 230V/50Hz</p> | 1166,40 |
|  | 2121221KSB500K2400V | <p>VENTS INLINE CENTRIFUGAL FAN IN INSULATED CASING KSB 500 K2 400V/50Hz</p> | 1188,00 |



Price Lists 03/04/2026

| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|--|------------------|---|----------------------|
|  | 2121221KSD250S4E | VENTS IN-LINE CENTRIFUGAL FAN KSD 250 S-4E Inline centrifugal fan with forward curved in sound- and thermal insulated casing Voltage: 230 V Sound pressure level at 3 m distance: 44 dBA Air capacity: 1520 m ³ /hr Power consumption: 243 W RPM: 1320 min-1 | 576,07 |
|  | 2121222ISB150 | BLAUBERG SOUND-INSULATED CENTR. BOX FAN ISO-B 150 Sound-insulated inline centrifugal fans. Maximum air flow up to 420 m ³ /h. | 257,50 |
|  | 2121222ISB200 | BLAUBERG SOUND-INSULATED CENTR. BOX FAN ISO-B 200 Sound-insulated inline centrifugal fan Maximum air capacity: 730 m ³ /hr Casing material: Galvanized steel Sound pressure level at 3 m: 38 dBA | 290,00 |
|  | 2121222ISB250 | BLAUBERG SOUND-INSULATED CENTR. BOX FAN ISO-B 250 Sound-insulated inline centrifugal fans Voltage: 230V Maximum air capacity: 1300 m ³ /hr Casing material: Galvanized steel Sound pressure level at 3 m: 41 dBA | 328,00 |






Price Lists 03/04/2026





| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|--|--------------------|--|----------------------|
|  <p>SOUND-INSULATED CENTR. BOX FAN ISO-B</p> | 2121222ISB315 | <p>BLAUBERG SOUND-INSULATED CENTR. BOX FAN ISO-B 315</p> <p>Sound-insulated inline centrifugal fan</p> <p>Voltage: 230V Maximum air capacity: 2150 m3/hr Casing material: Galvanized steel Sound pressure level at 3 m: 43 dBA</p> | 398,00 |
|  <p>BLAUBERG Box ISO-ZS 250 4E MAX</p> | 2121222ISZS2504EM | <p>BLAUBERG SOUND-INSULATED INLINE CENTR. BOX FAN ISO-ZS 250 4E MAX</p> <p>Maximum air capacity: 2470 m3/hr Casing material: Galvanized steel Sound pressure level at 3 m: 46 dBA</p> | 715,00 |
|  <p>BLAUBERG Box ISO-ZS 315 4E MAX</p> | 2121222ISZS3154EM | <p>BLAUBERG SOUND-INSULATED INLINE CENTR. BOX FAN ISO-ZS 315 4E MAX</p> <p>Sound-insulated inline centrifugal fan</p> <p>Voltage: 230 V Power: 931W Maximum air flow: 3520 m3/hr RPM: 1430 min-1</p> | 1002,00 |
|  <p>CENTRIFUGAL FAN FAMA</p> | 2121428F2004T400 | CENTRIFUGAL FAN FAMA 200 4T 0.5 HP 400V | 310,00 |
|  <p>CENTRIFUGAL FAN FAMA</p> | 2121428F2504T10400 | CENTRIFUGAL FAN FAMA 250 4T 1,0 HP 400V | 350,00 |







Price Lists 03/04/2026

| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|--|----------------------|---|----------------------|
|  | 2121428F2504T15400 | CENTRIFUGAL FAN FAMA 250 4T 1,5 HP 400V | 439,00 |
| | 2121428FB2004MT05230 | CENTRIFUGAL BOX FAN FAMA BOX 200 4M 0,5HP 230V | 473,00 |
|  | 2121522BOXD77A | DYNAIR BOX D 7/7 A6M 007KW FAN | 418,00 |
|  | 2121571BBD0909M4 | CASALS CENTRIFUGAL BOX FAN IN SOUNDPROOF CABINET BOX BD 9/9 M4 0.35kW 230V 50HZ | 515,00 |
|  | 2121571BBD1010M4 | CASALS CENTRIFUGAL BOX FAN IN SOUNDPROOF CABINET BOX BD 10/10 M4 0.59kW 230V 50HZ | 620,00 |
|  | 2121571BBD1212M6 | CASALS CENTRIFUGAL BOX FAN IN SOUNDPROOF CABINET BOX BD 12/12 M6 0.76kW 230V 50HZ | 815,00 |
|  | 2121571BD1515T6 | CASALS DOUBLE INLET FAN BD 15/15 T6 2,2kW | 1240,00 |

Price Lists 03/04/2026





| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|---|------------------|---|----------------------|
|  <p>VENTS AXIAL WALL FAN BS-125 MAO1</p> | 2123221BS125MAO1 | <p>VENTS AXIAL WINDOW FAN 125 MAO1</p> <p>Axial window fans for exhaust ventilation Maximum airflow: 185 m3/h Sound pressure level LpA at 3 m: 35 dB(A) Motor type: AC Casing material: Plastic</p> | 27,00 |
|  <p>VENTS AXIAL WALL FAN BS-150 MAO1</p> | 2123221BS150MAO1 | <p>VENTS AXIAL WINDOW FAN 150 MAO1</p> <p>Axial window fans for exhaust ventilation Maximum airflow: 295 m3/h Sound pressure level LpA at 3 m: 41 dB(A) Motor type: AC Casing material: Plastic</p> | 35,00 |
|  | 2123221VVR180 | <p>VENTS AXIAL WINDOW FAN VVR180</p> <p>Axial window fan with automatic louver shutters and reversing motor for exhaust and supply ventilation</p> <p>Voltage: 220-240V Power consumption: 25W Air capacity: 212 (exhaust)-176 (supply) m3/hr RPM: 1400</p> | 68,00 |
|  <p>BLAUBERG Axis-Q 200 2E</p> | 2123222AXQ2002E | <p>BLAUBERG AXIAL WALL FAN AXIS-Q 200 2E</p> <p>Axial wall fan</p> <p>Voltage:230V Maximum air flow: 800m3/hr Sound pressure level at 3 m: 38dBA Casing material: Polymer-coated steel RPM: 1380-1730 min-1</p> | 116,00 |

Price Lists 03/04/2026

| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|--|-----------------|---|----------------------|
|  | 2123222AXQ2504E | <p>BLAUBERG AXIAL WALL FAN AXIS-Q 250 4E</p> <p>Axial wall fan</p> <p>Voltage:230V Maximum air flow: 800m3/hr Sound pressure level at 3 m: 38dBA Casing material: Polymer-coated steel RPM: 1380-1730 min-1</p> | 127,00 |
|  | 2123222AXQ3004E | <p>BLAUBERG AXIAL WALL FAN AXIS-Q 300 4E</p> <p>Axial wall fan</p> <p>Voltage: 230V Maximum air flow: 1340 m3/hr Sound pressure level at 3 m: 44 dBA Casing material: Polymer-coated steel RPM: 1350-1405 min-1</p> | 145,00 |
|  | 2123222AXQ3504E | <p>BLAUBERG AXIAL WALL FAN AXIS-Q 350 4E</p> <p>Axial wall fan</p> <p>Voltage: 230V Maximum air flow: 2500 m3/hr Sound pressure level at 3 m: 46 dBA Casing material: Polymer-coated steel RPM: 1380-1700min-1</p> | 170,00 |
|  | 2123222AXQ4004E | <p>BLAUBERG AXIAL WALL FAN AXIS-Q 400 4E</p> <p>Axial wall fan</p> <p>Voltage:230V Maximum air flow: 3580 m3/hr Sound pressure level at 3 m: 53 dBA Casing material: Polymer-coated steel RPM: 1380-1655 min-1</p> | 205,00 |



Price Lists 03/04/2026

| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|--|-----------------|--|----------------------|
|  | 2123222AXQ5004E | BLAUBERG AXIAL WALL FAN AXIS-Q 500 4E Axial wall fan Voltage: 230V Maximum air flow: 7060 m3/hr Sound pressure level at 3 m: 58 dBA Casing material: Polymer-coated steel RPM: 1300-1630 min-1 | 275,00 |
|  | 2123522WI239AR | DYNAIR WINDOW 23/9 A REV. FAN - VITRO Wall Axial Fan Potentiated motor - Automatic / Without speed controller | 210,00 |
|  | 2123522WI3112AR | DYNAIR WINDOW 31/12A REV FAN - VITRO WINDOW AXIAL FAN Model: VITRO 12/300 800-1400 m3/h - 83Pa Power: 84W Noise: 59dBA IPX4 on external part only | 245,00 |
|  | 2124222TOH2202E | BLAUBERG CENTRIFUGAL ROOF FAN TOWER-H 220 2E Roof centrifugal fan Voltage: 230V Power: 108W Maximum air flow: 880 m3/hr RPM: 2580 min-1 | 249,00 |
| | | | |



Price Lists 03/04/2026





| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|--|------------------|--|----------------------|
|  | 2124222TOH2252E | BLAUBERG CENTRIFUGAL ROOF FAN TOWER-H 225 2E Roof centrifugal fan Voltage: 230V Power: 123W Maximum air flow: 915 m3/hr RPM: 2790 min-1 | 255,00 |
|  | 2124222TOH3104E | BLAUBERG CENTRIFUGAL ROOF FAN TOWER-H 310 4E Roof centrifugal fan Voltage: 230 V Power: 141 W Maximum air flow: 2265 m3/hr RPM: 1420 min-1 | 378,00 |
|  | 2124421FKTZB4200 | CENTRIFUGAL ROOF FAN FKTZB 4-200/012 Centrifugal roof fan - Motor: 230V/50Hz - Motor protection: IP: 54, Class: F - 1400 rpm - Power: 125Watt - Air volume: 950 m3/hr - Pressure: 180 Pa - Diameter: 200mm - Base dimensions: 350x350mm | 420,00 |
|  | 2124522REA202M | CENTRIFUGAL MUSHROOM ROOF FAN REA 202M 0.06KW | 261,45 |



Price Lists 03/04/2026

| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|--|-------------------|---|----------------------|
|  <p>REAR</p> | 2124522REA252 | CENTR. MUSHROOM FAN REA 252M | 336,80 |
|  <p>MRF-BA</p> | 2124523MRF100 | CENTRIFUGAL ROOF FAN MRF 100 BA Centrifugal roof fan | 265,00 |
|  <p>MRF</p> | 2124523MRF250 | CENTRIFUGAL ROOF FAN MRF 250 | 184,84 |
|  <p>MRF-BA</p> | 2124523MRF250BA | CENTRIFUGAL ROOF FAN MRF 250BA WITH BASE With square roof curb | 289,00 |
|  <p>VCUN</p> | 2126221VCUN140X74 | VENTS CENTRIFUGAL FAN VCUN 140X74 - 0,37-2 R (3PHASE) | 238,14 |
|  <p>VCUN</p> | 2126221VCUN20093 | VENTS CENTRIFUGAL FAN VCUN 200X93 - 0,55-4 R (3PHASE) | 328,86 |
| | | | |

Price Lists 03/04/2026

| Photo | ARIMEC Code | Description | Price (EUR) + VAT |
|--|-----------------|--|----------------------|
|  | 2131571FOCCETA | CASALS ROOF CHIMNEY FAN FOCCETA 0.12KW 230V Centrifugal roof fan - Motor: 230V/50Hz - Motor protection: IP X4, Class: I - 1400 rpm - Power: 0.12kW - Air volume: 750 m3/hr - Pressure: 180 Pa - I max (230V): 0.5A - Base dimensions: 400x400mm | 590,00 |
|  | 2133222BOXS454D | BLAUBERG BOX-S 45-4D/0.75-80X60 SMOKE EXTRACTION FAN Duct smoke extraction fan | 1350,00 |
| | 2133222BOXS504D | BLAUBERG BOX-S 50-4D/1.5-80X60 SMOKE EXTRACTION FAN Duct smoke extraction fan | 1564,00 |
|  | 2133222BOXS564D | BLAUBERG BOX-S 56-4D/3-90X70 SMOKE EXTRACTION FAN Duct smoke extraction fan | 1755,00 |
|  | 2133222BOXS634D | BLAUBERG BOX-S 63-4D/4-100X80 SMOKE EXTRACTION FAN Duct smoke extraction fan | 2075,00 |