







Price Lists 11/05/2026

Photo	ARIMEC Code	Description	Price (EUR) + VAT
	2112221TT100	<p>VENTS MIXED FLOW FAN TT100</p> <p>Inline mixed flow fan</p> <p>Sound pressure level at 3 m distance: 27 - 36 dBA Power consumption: 21- 33 W Maximum air capacity: 145 - 187 m³/h RPM: 2180 - 2385 min-1</p>	53,30
	2112221TT100T	<p>VENTS MIXED FLOW FAN TT100 TIMER</p> <p>Inline mixed flow fan with time delay</p> <p>Sound pressure level at 3 m distance: 27 - 36 dBA Power consumption: 21- 33 W Maximum air capacity: 145 - 187 m³/h RPM: 2180 - 2385 min-1</p>	72,58
	2112221TT125	<p>VENTS MIXED FLOW FAN TT125</p> <p>Inline mixed flow fan</p> <p>Voltage: 1~230 V Maximum air capacity: 220 - 280 m³/h Power consumption: 23 - 37 W RPM: 1950 - 2455 min-1</p>	57,83
	2112221TT125S	<p>VENTS MIXED FLOW FAN TT125 S</p> <p>Inline mixed flow fan</p> <p>Voltage: 1~230 V Maximum air capacity: 295 - 440 m³/h Power consumption: 32 - 60 W RPM: 1850 - 2510 min-1</p>	79,38

Price Lists 11/05/2026

Photo	ARIMEC Code	Description	Price (EUR) + VAT
 <p>TT</p> <p>BLAUBERG VENTS 2112</p>	2112221TT125ST	VENTS MIXED FLOW FAN TT125 ST	107,00
 <p>TT</p> <p>BLAUBERG VENTS 2112</p>	2112221TT125T	VENTS MIXED FLOW FAN TT125 TIMER Inline mixed flow fan with time delay Voltage: 1~230 V Maximum air capacity: 220 - 280 m³/h Power consumption:23 - 37 W RPM: 1950 - 2455 min-1	75,98
 <p>TT</p> <p>BLAUBERG VENTS 2112</p>	2112221TT125U	VENTS MIXED FLOW FAN TT125 U with temp sensor	96,39
 <p>TT</p> <p>BLAUBERG VENTS 2112</p>	2112221TT150	VENTS MIXED FLOW FAN TT150 Inline mixed flow fan Voltage: 1~230 V Maximum air capacity: 405 - 520 m³/h Power consumption:29 - 60 W RPM: 1680 - 2460 min-1	102,06
 <p>TT PRO</p> <p>BLAUBERG VENTS 2112</p>	2112221TTPRO100	VENTS INLINE MIXED-FLOW FAN TT100 PRO Inline mixed flow fan Voltage: 1~230 V Sound pressure level at 3 m distance: 27 - 32 dBA Power consumption: 23 - 25 W Maximum air capacity: 180 - 245 m³/h RPM: 2050 -2620 min-1	86,10






Price Lists 11/05/2026

Photo	ARIMEC Code	Description	Price (EUR) + VAT
 <p>TT PRO 2112</p>	2112221TTPRO200T	<p>VENTS INLINE MIXED-FLOW FAN TT200 PRO TIMER</p> <p>Voltage: 230V Power: 76-108W Current: 0.34-0.48A Max, Air Flow: 830-1040 m3/h RPM: 1915-2380 mn-1 Noise Level at 3m: 39-45dBA Transported Air Temp.: 60o SEC Class: B Protection Rating: IPX4 T: Adjustable timer from 2 to 30 minutes</p>	187,11
 <p>TT PRO 2112</p>	2112221TTPRO250T	<p>VENTS INLINE MIXED-FLOW FAN TT250 PRO TIMER</p> <p>Voltage: 230V Power: 125-177W Current: 0.54-0.79A Max, Air Flow: 1110-1400 m3/h RPM: 1955-2440 mn-1 Noise Level at 3m: 44-51dBA Transported Air Temp.: 60o Protection Rating: IPX4 T: Adjustable timer from 2 to 30 minutes</p>	255,15
 <p>TT PRO 2112</p>	2112221TTPRO315	<p>VENTS INLINE MIXED-FLOW FAN TT315 PRO</p> <p>Voltage: 230V Power: 230-320W Current: 1.0-1.42A Max, Air Flow: 1570-2050 m3/h RPM: 1890-2430 mn-1 Noise Level at 3m: 41-52dBA Transported Air Temp.: 60o Protection Rating: IPX4</p>	312,98

Price Lists 11/05/2026

Photo	ARIMEC Code	Description	Price (EUR) + VAT
 <p>TT Silent-M</p> <p><small>BLAUBERG VENTS 2112</small></p>	2112221TTSM100	<p>VENTS INLINE MIXED-FLOW FAN TT SILENT-M 100</p> <p>Inline mixed-flow fans in sound- and heat-insulated casing</p> <p>Voltage: 230V Power consumption: 24-26W Air capacity: 170 (exhaust)-240 (supply) m3/hr RPM: 2030-2630 min-1</p>	167,00
 <p>TT Silent-M</p> <p><small>BLAUBERG VENTS 2112</small></p>	2112221TTSM100T	<p>VENTS INLINE MIXED-FLOW FAN TT SILENT-M 100 T</p> <p>Inline mixed-flow fans in sound- and heat-insulated casing with time delay</p> <p>Voltage: 230V Power consumption: 24-26W Air capacity: 170 (exhaust)-240 (supply) m3/hr RPM: 2030-2630 min-1</p>	185,00
 <p>TT Silent-M</p> <p><small>BLAUBERG VENTS 2112</small></p>	2112221TTSM125	<p>VENTS INLINE MIXED-FLOW FAN TT SILENT-M 125</p> <p>Inline mixed-flow fans in sound- and heat-insulated casing.</p> <p>Voltage: 230V Power consumption: 25-29W Air capacity: 230 (exhaust)-340 (supply) m3/hr RPM: 2650-2310 min-1</p>	170,00
 <p>TT Silent-M</p> <p><small>BLAUBERG VENTS 2112</small></p>	2112221TTSM125T	<p>VENTS INLINE MIXED-FLOW FAN TT SILENT-M 125 T</p> <p>Inline mixed-flow fans in sound- and heat-insulated casing with time delay</p> <p>Voltage: 230V Power consumption: 25-29W Air capacity: 230 (exhaust)-340 (supply) m3/hr RPM: 2650-2310 min-1</p>	187,00






Price Lists 11/05/2026

Photo	ARIMEC Code	Description	Price (EUR) + VAT
 <p>TT Silent-M</p> <p><small>BLAUBERG VENTS 2112</small></p>	2112221TTSM200	<p>VENTS INLINE MIXED-FLOW FAN TT SILENT-M 200</p> <p>Inline mixed-flow fans in sound- and heat-insulated casing.</p> <p>Voltage: 230V Power consumption: 78-110W Air capacity: 810 (exhaust)-1020 (supply) m3/hr RPM: 2015-2445 min-1</p>	258,00
 <p>TT Silent-M</p> <p><small>BLAUBERG VENTS 2112</small></p>	2112221TTSM200T	<p>VENTS INLINE MIXED-FLOW FAN TT SILENT-M 200 T</p> <p>Inline mixed-flow fans in sound- and heat-insulated casing with time delay</p> <p>Voltage: 230V Power consumption: 78-110W Air capacity: 810 (exhaust)-1020 (supply) m3/hr RPM: 2015-2445 min-1</p>	277,00
 <p>VKM</p> <p><small>BLAUBERG VENTS 2112</small></p>	2112221VKM100	<p>VENTS CENTRIFUGAL IN-LINE VKM 100</p>	142,88
 <p>VKM</p> <p><small>BLAUBERG VENTS 2112</small></p>	2112221VKM150	<p>VENTS CENTRIFUGAL IN-LINE VKM 150</p>	165,56
 <p>VENTS CENTRIFUGAL IN-LINE VKM 160 GREY</p> <p><small>BLAUBERG VENTS</small></p>	2112221VKM160	<p>VENTS CENTRIFUGAL IN-LINE VKM 160 GREY</p>	55,00

Price Lists 11/05/2026

Photo	ARIMEC Code	Description	Price (EUR) + VAT
 <p>VKM 2112</p>	2112221VKM200	VENTS CENTRIFUGAL IN-LINE VKM 200	216,59
	2112221VKO1K100T	VENTS VENTILATION 100 VKO1k TURBO Axial inline fan Voltage: 220-240 V Sound pressure level at 3 m distance: 37 dBA Power consumption: 16 W Maximum air capacity: 137 m³/h RPM: 2300 min-1	26,08
	2112221VKO1K125	VENTS AXIAL IN-LINE FAN 125 VKO1K	24,95
	2112221VKO1TK125	VENTS AXIAL IN-LINE FAN 125 VKO1TK	31,75
 <p>TURBO 100</p>	2112222TU100	BLAUBERG TURBO 100	74,00
 <p>TURBO 100T</p>	2112222TU100T	BLAUBERG TURBO 100 T	89,00




Price Lists 11/05/2026

Photo	ARIMEC Code	Description	Price (EUR) + VAT
 <p>TURBO 125T</p>	2112222TU125T	BLAUBERG TURBO 125 T	92,00
 <p>TURBO 150</p>	2112222TU150	BLAUBERG TURBO 150	101,45
 <p>TURBO 150T</p>	2112222TU150T	BLAUBERG TURBO 150 T	122,00
 <p>TURBO 200</p>	2112222TU200	BLAUBERG TURBO 200 Inline mixed-flow fan Voltage: 230V Power consumption: 76-108W Air capacity: 805 (exhaust)-1080 (supply) m3/hr RPM: 1915-2380 min-1	125,00
 <p>TURBO 250</p>	2112222TU250	BLAUBERG TURBO 250 Inline mixed-flow fan Voltage: 220-2400V Power consumption: 125-177W Air capacity: 1070 min - 1360 max m3/hr RPM: 1955-2440 min-1	235,00





Price Lists 11/05/2026

Photo	ARIMEC Code	Description	Price (EUR) + VAT
 <p>TURBO 250T</p>	2112222TU250T	BLAUBERG TURBO 250 T	255,00
 <p>TURBO 315T</p>	2112222TU315T	BLAUBERG TURBO 315T	330,00
 <p>WAVE</p>	2112222WAVE100125	BLAUBERG SOUND INSULATED MIXED-FLOW FAN IN WAVE 100/125	155,00
 <p>WAVE</p>	2112222WAVE150160	BLAUBERG SOUND INSULATED MIXED-FLOW FAN IN WAVE 150/160	179,00
	2112583LINQ125	VORTICE SOUND-PROOF MIXED FLOW FAN LINEO 125 QUIET	141,00
	2112583LINQ125T	VORTICE SOUND-PROOF MIXED FLOW FAN LINEO 125 T QUIET With time delay	160,00






Price Lists 11/05/2026

Photo	ARIMEC Code	Description	Price (EUR) + VAT
 <p>KSB</p> <p>2121</p>	2121221KSB100	<p>VENTS SOUND INSULATED BOX FAN KSB100</p> <p>Compact inline sound- and heat-insulated centrifugal fan with back-curved impeller blades</p> <p>Voltage: 230 V Sound pressure level at 3 m distance: 33 - 34 dBA Power consumption: 73 - 77 W Maximum air capacity: 240 - 255 m³/h RPM: 2560 - 2690 min-1</p>	203,72
 <p>SOUND INSULATED BOX FAN KSB100 K2</p>	2121221KSB100K2	<p>VENTS SOUND INSULATED BOX FAN KSB100 K2</p> <p>Compact inline sound- and heat-insulated centrifugal fan with back-curved impeller blades</p> <p>Voltage: 230 V Sound pressure level at 3 m distance: 33 - 34 dBA Power consumption: 73 - 77 W Maximum air capacity: 240 - 255 m³/h RPM: 2560 - 2690 min-1</p>	125,00
 <p>SOUND INSULATED BOX FAN KSB125 K2</p>	2121221KSB125K2	<p>VENTS SOUND INSULATED BOX FAN KSB125 K2</p> <p>Inline centrifugal fans in heat- and sound-insulated casing Maximum airflow: 330 m3/h</p>	140,00
	2121221KSB125K2S	<p>VENTS SOUND INSULATED BOX FAN KSB125 K2 S - HIGH POWERED MOTOR</p> <p>Inline centrifugal fans in heat- and sound-insulated casing Maximum airflow: 484 m3/h Sound pressure level LpA at 3 m: 40 dB(A)</p>	160,00

Price Lists 11/05/2026

Photo	ARIMEC Code	Description	Price (EUR) + VAT
	2121221KSB150	<p>VENTS SOUND INSULATED BOX FAN KSB150</p> <p>Compact inline sound- and heat-insulated centrifugal fan with back-curved impeller blades</p> <p>Voltage: 230V Power consumption: 72-76W Air capacity: 420 (exhaust)-435 (supply) m3/hr RPM: 2600-2720 min-?</p>	221,13
	2121221KSB150K2	<p>VENTS SOUND INSULATED BOX FAN KSB150 K2</p> <p>Inline centrifugal fans in heat- and sound-insulated casing Maximum airflow: 485 m3h Sound pressure level LpA at 3 m: 38 dB(A)</p>	170,00
	2121221KSB160K2	<p>VENTS SOUND INSULATED BOX FAN KSB160 K2</p> <p>Inline centrifugal fans in heat- and sound-insulated casing Maximum airflow: 500 m3/h Sound pressure level LpA at 3 m: 38 dB(A)</p>	180,00
	2121221KSB200K2	<p>VENTS SOUND INSULATED BOX FAN KSB200 K2</p> <p>Inline centrifugal fans in heat- and sound-insulated casing Maximum airflow: 770 m3/h Sound pressure level LpA at 3 m: 42 dB(A)</p>	250,00
	2121221KSB200S	<p>VENTS SOUND INSULATED BOX FAN KSB200S</p> <p>Compact inline sound- and heat-insulated centrifugal fan with back-curved impeller blades</p> <p>Voltage: 230 V Power consumption: 195 - 1232 W Air capacity: 950 (exhaust) - 960 (supply) m3/hr RPM: 2570 - 2690 min-1</p>	280,10





Price Lists 11/05/2026

Photo	ARIMEC Code	Description	Price (EUR) + VAT
 <p>KSB</p>	2121221KSB250	<p>VENTS SOUND INSULATED BOX FAN KSB250</p> <p>Compact inline sound- and heat-insulated centrifugal fan with back-curved impeller blades</p> <p>Voltage: 230 V Power consumption: 198 - 238 W Air capacity: 1300 (exhaust) - 1315 (supply) m3/hr RPM: 2420 - 2730 min-1</p>	300,86
 <p>SOUND INSULATED BOX FAN KSB250 K2</p>	2121221KSB250K2	<p>VENTS SOUND INSULATED BOX FAN KSB250 K2</p> <p>Inline centrifugal fans in heat- and sound-insulated casing Maximum airflow: 1515 m3/h Sound pressure level LpA at 3 m: 45 dB(A) Sound insulation</p>	300,00
 <p>SOUND INSULATED BOX FAN KSB315 K2S</p>	2121221KSB315K2S	<p>VENTS SOUND INSULATED BOX FAN KSB315 K2 S - HIGH POWERED MOTOR</p> <p>Inline centrifugal fans in heat- and sound-insulated casing Maximum airflow: 2710 m3/h Sound pressure level LpA at 3 m: 48 dB(A)</p>	434,00
 <p>SOUND INSULATED BOX FAN KSB355 K2</p>	2121221KSB355K2	<p>VENTS SOUND INSULATED BOX FAN KSB355 K2</p> <p>Inline centrifugal fans in heat- and sound-insulated casing Maximum airflow: 2235 m3/h Sound pressure level LpA at 3 m: 48 dB(A)</p>	350,00
 <p>SOUND INSULATED BOX FAN KSB400 K2</p>	2121221KSB400K2	<p>VENTS INLINE CENTRIFUGAL FAN IN INSULATED CASING KSB 400 K2</p>	691,20

Price Lists 11/05/2026

Photo	ARIMEC Code	Description	Price (EUR) + VAT
 <p>SOUND INSULATED BOX FAN KSB400 K2 Q</p>	2121221KSB450K2Q	<p>VENTS SOUND INSULATED BOX FAN KSB450 K2 Q - LOW NOISE</p> <p>Inline centrifugal fan in heat- and sound-insulated casing with air flow up to 2760 m³/h. Q: low noise and low-powered motor</p>	615,00
 <p>KSB</p>	2121221KSB500K2230V	VENTS INLINE CENTRIFUGAL FAN IN INSULATED CASING KSB 500 K2 230V/50Hz	1166,40
 <p>KSB</p>	2121221KSB500K2400V	VENTS INLINE CENTRIFUGAL FAN IN INSULATED CASING KSB 500 K2 400V/50Hz	1188,00
	2121221KSD250S4E	<p>VENTS IN-LINE CENTRIFUGAL FAN KSD 250 S-4E</p> <p>Inline centrifugal fan with forward curved in sound- and thermal insulated casing</p> <p>Voltage: 230 V Sound pressure level at 3 m distance: 44 dBA Air capacity: 1520 m³/hr Power consumption: 243 W RPM: 1320 min-1</p>	576,07
 <p>BLAUBERG Iso-B 150</p>	2121222ISB150	<p>BLAUBERG SOUND-INSULATED CENTR. BOX FAN ISO-B 150</p> <p>Sound-insulated inline centrifugal fans. Maximum air flow up to 420 m³/h.</p>	257,50





Price Lists 11/05/2026

Photo	ARIMEC Code	Description	Price (EUR) + VAT
	2121222ISB200	<p>BLAUBERG SOUND-INSULATED CENTR. BOX FAN ISO-B 200</p> <p>Sound-insulated inline centrifugal fan</p> <p>Maximum air capacity: 730 m3/hr Casing material: Galvanized steel Sound pressure level at 3 m: 38 dBA</p>	290,00
	2121222ISB250	<p>BLAUBERG SOUND-INSULATED CENTR. BOX FAN ISO-B 250</p> <p>Sound-insulated inline centrifugal fans</p> <p>Voltage: 230V Maximum air capacity: 1300 m3/hr Casing material: Galvanized steel Sound pressure level at 3 m: 41 dBA</p>	328,00
	2121222ISB315	<p>BLAUBERG SOUND-INSULATED CENTR. BOX FAN ISO-B 315</p> <p>Sound-insulated inline centrifugal fan</p> <p>Voltage: 230V Maximum air capacity: 2150 m3/hr Casing material: Galvanized steel Sound pressure level at 3 m: 43 dBA</p>	398,00
	2121222ISZS2504EM	<p>BLAUBERG SOUND-INSULATED INLINE CENTR. BOX FAN ISO-ZS 250 4E MAX</p> <p>Maximum air capacity: 2470 m3/hr Casing material: Galvanized steel Sound pressure level at 3 m: 46 dBA</p>	715,00

Price Lists 11/05/2026

Photo	ARIMEC Code	Description	Price (EUR) + VAT
 <p>BLAUBERG Box ISO-ZS 315 4E MAX</p>	2121222ISZS3154EM	<p>BLAUBERG SOUND-INSULATED INLINE CENTR. BOX FAN ISO-ZS 315 4E MAX</p> <p>Sound-insulated inline centrifugal fan</p> <p>Voltage: 230 V Power: 931W Maximum air flow: 3520 m3/hr RPM: 1430 min-1</p>	1002,00
 <p>CENTRIFUGAL FAN FAMA</p>	2121428F2004T400	CENTRIFUGAL FAN FAMA 200 4T 0.5 HP 400V	310,00
 <p>CENTRIFUGAL FAN FAMA</p>	2121428F2504T10400	CENTRIFUGAL FAN FAMA 250 4T 1,0 HP 400V	350,00
 <p>CENTRIFUGAL FAN FAMA</p>	2121428F2504T15400	CENTRIFUGAL FAN FAMA 250 4T 1,5 HP 400V	439,00
	2121428FB2004MT05230	CENTRIFUGAL BOX FAN FAMA BOX 200 4M 0,5HP 230V	473,00
 <p>BOX-D</p>	2121522BOXD77A	DYNAIR BOX D 7/7 A6M 007KW FAN	418,00

Price Lists 11/05/2026

Photo	ARIMEC Code	Description	Price (EUR) + VAT
<p>CENTRIFUGAL BOX FAN IN SOUNDPROOF CABINET BOX BD 9/9 M4</p>  <p>Casals</p>	2121571BBD0909M4	<p>CASALS CENTRIFUGAL BOX FAN IN SOUNDPROOF CABINET BOX BD 9/9 M4 0.35kW</p> <p>230V 50HZ</p>	515,00
<p>CENTRIFUGAL BOX FAN IN SOUNDPROOF CABINET BOX BD 10/10 M4 0.59kW</p>  <p>Casals</p>	2121571BBD1010M4	<p>CASALS CENTRIFUGAL BOX FAN IN SOUNDPROOF CABINET BOX BD 10/10 M4 0.59kW</p> <p>230V 50HZ</p>	620,00
<p>CENTRIFUGAL BOX FAN IN SOUNDPROOF CABINET BOX BD 12/12 M6 0.76kW</p>  <p>Casals</p>	2121571BBD1212M6	<p>CASALS CENTRIFUGAL BOX FAN IN SOUNDPROOF CABINET BOX BD 12/12 M6 0.76kW</p> <p>230V 50HZ</p>	815,00
<p>CENTRIFUGAL BOX FAN IN SOUNDPROOF CABINET BOX BD 15/15 T6 2,2kW</p>  <p>Casals</p>	2121571BD1515T6	<p>CASALS DOUBLE INLET FAN BD 15/15 T6 2,2kW</p>	1240,00